

**DRAC DP 20****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**General ordering data**

Local product	Only available in certain countries
Type	DRAC DP 20
Order No.	<a href="#">7940084719</a>
US order No.	6720005420
Version	DIN rail socket

**DRAC DP 20****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Technical data****General ordering data**

Local product	Only available in certain countries
---------------	-------------------------------------

**Local features**

Availability	United States
--------------	---------------

**DIN-Rail Receptacles**

Current Interrupting	10 kA	Dielectric voltage	Withstands 2000V per UL498
Flame resistance, housing cover	Polyamide, 6/6 30% GF, UL94 nominal value V0 at 0.63 mm	Flame resistance, housing floor	PBT / Polycarbonate mixture, UL94 nominal value V0 at 0.63 mm
Frequency range, max.	60 Hz	Frequency range, min.	50 Hz
Max. torque for main contact	7 Nm	Spring	Stainless Steel
Trip Level	5 +/- 1 mA	Wire connection cross section AWG, max.	AWG 10
Wire connection cross section AWG, min.	AWG 20		

**Rated data**

Rated current	20 A	Rated voltage	125 V
---------------	------	---------------	-------