

**DRAC GF 15****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**General ordering data**

Local product	Only available in certain countries
Type	DRAC GF 15
Order No.	<a href="#">7940084721</a>
US order No.	6720005422
Version	DIN rail socket

## DRAC GF 15

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technische Daten

### General ordering data

Local product Only available in certain countries

### Local features

Availability United States

### DIN-Rail Receptacles

Current Interrupting	Full rated current	Dielectric voltage	Withstands 1500V per UL498
Flame resistance, housing cover	Polyamide, 6/6 30% GF, UL94 nominal value V0 at 0.63 mm	Flame resistance, housing floor	PBT / Polycarbonate mixture, UL94 nominal value V0 at 0.63 mm
Frequency range, max.	60 Hz	Frequency range, min.	50 Hz
Max. torque for main contact	7 Nm	Spring	Stainless Steel
Wire connection cross section AWG, max.	AWG 10	Wire connection cross section AWG, min.	AWG 20

### Rated data

Rated current 15 A Rated voltage 125 V